



## 2016 FOURTRAX RANCHER 4X4 AUTOMATIC DCT IRS EPS SPECIFICATIONS\*

ENGINE	
Engine Type	420cc liquid-cooled fuel-injected OHV wet-sump longitudinally mounted single-cylinder four-stroke
Bore And Stroke	86.5mm x 71.5mm
Induction	Keihin® 33mm throttle-body fuel-injection system
Ignition	Full-transistorized type with electronic advance
Starter	Electric with optional auxiliary recoil
Compression Ratio	9.9:1
DRIVE TRAIN	
Clutch	Automatic
Transmission	Automatic DCT with Reverse
Driveline	Direct front and rear driveshafts with TraxLok® and torque-sensitive front differential
CHASSIS / SUSPENSION / BRAKES	
Front Suspension	Independent double-wishbone; 7.28 inches travel
Rear Suspension	Independent dual-arm; 8.46 inches travel
Front Brake	190mm Dual hydraulic disc
Rear Brake	170mm Hydraulic disc
Front Tire	24 x 8-12
Rear Tire	24 x 10-11
DIMENSION	
Length	84.6 inches
Width	47.4 inches
Height	46.8 inches
Wheelbase	50.9 inches
Seat Height	34.9 inches
Ground Clearance	9.2 inches
Curb Weight	686 pounds (Includes all standard equipment, required fluids and a full tank of fuel—ready to ride)
Fuel Capacity	3.9 gallons, including 1.3-gallon reserve
Turning Radius	11.5 feet
OTHER	
Model Id	TRX420FA6
Emissions	Meets current California Air Resources Board (CARB) and EPA off-road emissions standards
Available Colors	Red, White, Honda Phantom Camo®
Note	No operator under age 16. Honda recommends that all ATV riders take a training course and read their owners manual thoroughly.
FACTORY WARRANTY INFORMATION	
One Year	Transferable limited warranty; extended coverage available with a Honda Protection Plan