

MAINTENANCE SCHEDULE

Perform the Pre-ride Inspection (page 33) at each scheduled maintenance period.

I : INSPECT AND CLEAN, ADJUST, LUBRICATE OR REPLACE IF NECESSARY

C: CLEAN R: REPLACE A: ADJUST L: LUBRICATE

ITEM	FREQUENCY	WHICHEVER COMES FIRST ↓	ODOMETER READING [NOTE 3]				Refer to
			1,000 km (600 mi)	6,000 km (3,600 mi)	12,000 km (7,200 mi)	18,000 km (10,800 mi)	
* FUEL LINE		EVERY		I	I	I	
* FUEL STRAINER			C	C	C	C	
* THROTTLE OPERATION & OIL PUMP SYNCHRONIZATION			I	I	I	I	
* CARBURETOR-CHOKE				I	I	I	
AIR CLEANER	NOTE 1			C	C	C	Page 57
SPARK PLUGS				R	R	R	Page 55
* ENGINE OIL FILTER	YEAR	C		C			
TRANSMISSION OIL		R		R			Pages 53—54
* CARBURETOR-IDLE SPEED		I	I	I	I	I	
* CARBURETOR SYNCHRONIZATION		I	I	I	I	I	
RADIATOR COOLANT			I	I	*R		Pages 31—32
* RADIATOR CORE			I	I	I	I	
* H. & C. OF COOLING SYSTEM			I	I	I	I	