

		FRONT	REAR
TYRE SIZE		AT24 × 8-11 ★★	AT24 × 10-11 ★★
TYRE BRAND		TRACKER ATT GOOD YEAR	TRACKER ATT GOOD YEAR
NO CARGO	RECOMMENDED PRESSURE	25 kPa (0.25 kgf/cm ² , 3.6 psi)	25 kPa (0.25 kgf/cm ² , 3.6 psi)
	MAXIMUM PRESSURE	28 kPa (0.28 kgf/cm ² , 4.0 psi)	28 kPa (0.28 kgf/cm ² , 4.0 psi)
	MINIMUM PRESSURE	22 kPa (0.22 kgf/cm ² , 3.2 psi)	22 kPa (0.22 kgf/cm ² , 3.2 psi)
WITH CARGO	RECOMMENDED PRESSURE	25 kPa (0.25 kgf/cm ² , 3.6 psi)	25 kPa (0.25 kgf/cm ² , 3.6 psi)

Fig. 4-34

Tyre specifications

⚠ WARNING

POTENTIAL HAZARD

Operating this ATV with improper tyres, or with uneven tyre pressure.

WHAT CAN HAPPEN

Use of improper tyres on this ATV, or operation of this ATV with improper or uneven tyre pressure, may cause loss of control, increasing your risk of an accident.

HOW TO AVOID THE HAZARD

Always use the size and type tyres specified in this Owner's Manual for this vehicle.

Always maintain proper tyre pressure as described in this Owner's Manual.