

# Specifications

| <b>Chassis &amp; Suspension</b>            |  |
|--|--|
| caster                                     | 3.0°   |
| trail                                      | 0.3 in (7 mm)                                |
| tire size, front                           | AT25 × 8-12 ★★                               |
| tire size, rear                            | AT25 × 10-12 ★★                              |
| tire pressure, front & rear (cold)         | 3.6 psi (25 kPa , 0.25 kgf/cm <sup>2</sup> ) |
| maximum tire pressure, front & rear (cold) | 4.0 psi (28 kPa , 0.28 kgf/cm <sup>2</sup> ) |
| minimum tire pressure, front & rear (cold) | 3.2 psi (22 kPa , 0.22 kgf/cm <sup>2</sup> ) |

| <b>Electrical</b> |                    |
|-------------------|--------------------|
| battery           | 12 V – 12 Ah       |
| generator         | 0.326 kW/5,000 rpm |

| <b>Lights</b>                  |                  |
|--------------------------------|------------------|
| headlight (low/high)           | 12 V 30/30 W × 2 |
| assist headlight               | 12 V 45 W        |
| tail light                     | 12 V 5 W × 2     |
| neutral indicator              | LED              |
| reverse indicator              | LED              |
| oil high temperature indicator | LED              |
| 4WD indicator                  | LED              |