

Specifications

■ Main Components

Type	NC52
Overall length	80.1 in (2,035 mm)
Overall width	29.9 in (760 mm)
Overall height	41.1 in (1,045 mm)
Wheelbase	54.3 in (1,380 mm)
Minimum ground clearance	5.9 in (150 mm)
Caster angle	25.1°
Trail	3.9 in (98 mm)
Curb weight	CB300F 348 lb (158 kg)
	CB300FA 355 lb (161 kg)
Maximum weight capacity*1	366 lb (166 kg)
Passenger capacity	Rider and 1 passenger
Minimum turning radius	8.2 ft (2.5 m)

*1 Including rider, passenger, all luggage, and accessories

Displacement	17.4 cu-in (286 cm ³)
Bore x stroke	2.99 x 2.48 in (76.0 x 63.0 mm)
Compression ratio	10.7:1
Fuel	Unleaded gasoline Recommended fuel octane number: Pump Octane Number (PON) 86 or higher.
Tank capacity	3.43 US gal (13.0 liters)
Battery	YTX7L-BS 12V-6Ah (10 HR)
Gear ratios	1st 3.416
	2nd 2.250
	3rd 1.650
	4th 1.350
	5th 1.166
	6th 1.038
Reduction ratios (primary / final)	2.807 / 2.571