







Maintenance Schedule

| Items | | Frequency*1 | | | | | | | | Regular Replace | Refer to page |
|----------------------------|--------------------------|---|-----|----------|----------|----------|----------|----------|----------|-----------------|---------------|
| | | x 1,000 mi | 0.6 | 4 | 8 | 12 | 16 | 20 | 24 | | |
| | | x 1,000 km | 1.0 | 6.4 | 12.8 | 19.2 | 25.6 | 32.0 | 38.4 | | |
| Non-Emission-Related Items | Drive Chain*5 | Every 600 mi (1,000 km): I L | | | | | | | | | 117 |
| | Drive Chain Slider | | | I | I | I | I | I | I | | 120 |
| | Brake Fluid*7 | | | I | I | I | I | I | I | 2 Years | 112 |
| | Brake Pads Wear | | | I | I | I | I | I | I | | 113 |
| | Brake System | | | | I | | I | | I | | 112 |
| | Brake Light Switch | | | | I | | I | | I | | 115 |
| | Brake Lock Operation*8 |  | | I | I | I | I | I | I | | 114 |
| | Headlight Aim | | | | I | | I | | I | | 127 |
| | Clutch System*9 | | | I | I | I | I | I | I | | 122 |
| | Side Stand | | | | I | | I | | I | | 116 |
| | Suspension |  | | | I | | I | | I | | - |
| | Spark Arrester*6 |  | | C | C | C | C | C | C | C | 102 |
| | Nuts, Bolts, Fasteners*5 |  | | | I | | I | | I | | - |
| | Wheels/Tires*5 |  | | I | I | I | I | I | I | | 90 |
| | Steering Head Bearings |  | | | I | | I | | I | | - |

Notes:

- *1 : At higher odometer readings, repeat at the frequency interval established here.
- *2 : Service more frequently when riding in unusually wet or dusty areas.
- *3 : Service more frequently when riding in rain or at full throttle.
- *4 : 50 STATE (meets California).

- *5 : Service more frequently when riding OFF-ROAD.
- *6 : USA only.
- *7 : Replacement requires mechanical skill.
- *8 : DCT type only.
- *9 : Except DCT type.