

Specifications

Cooling system capacity	1.74 US qt (1.65 L)	
Recommended coolant	Pro Honda HP Coolant	
Recommended drive chain lubricant	Pro Honda HP Chain Lube or equivalent	
Drive chain slack	CRF1000A/D	1 3/8 - 1 3/4 in (35 - 45 mm)
	CRF1000A II/D II	1 3/4 - 2 3/16 in (45 - 55 mm)
Standard drive chain	DID 525HV3	
	No. of links	124
Standard sprocket size	Drive sprocket	16T
	Driven sprocket	42T

■ Bulbs

Headlight	LED
Brake light/Taillight	LED
Front turn signal	LED
Rear turn signal	LED
Position light	LED
License plate light	12 V-5 W

■ Fuses

Main fuse	30 A
Other fuse	30 A, 20 A, 15 A, 10 A

■ Torque Specifications

Right side lid bolt CRF1000A II/D II	0.3 lbf-ft (0.42 N-m, 0.04 kgf-m)
Skid plate bolt	19 lbf-ft (26 N-m, 2.7 kgf-m)
Spark arrester mounting bolt	6.6 lbf-ft (9.0 N-m, 0.9 kgf-m)
Pan screw	6.6 lbf-ft (9.0 N-m, 0.9 kgf-m)
Tail cap cover bolt	6.6 lbf-ft (9.0 N-m, 0.9 kgf-m)
Oil filter	19 lbf-ft (26 N-m, 2.7 kgf-m)
Engine oil drain bolt	22 lbf-ft (30 N-m, 3.1 kgf-m)
Clutch oil filter cover bolt CRF1000D/D II	9 lbf-ft (12 N-m, 1.2 kgf-m)
Rear wheel axle nut	74 lbf-ft (100 N-m, 10.2 kgf-m)
Drive chain adjusting lock nut	20 lbf-ft (27 N-m, 2.8 kgf-m)
Front wheel axle nut	44 lbf-ft (60 N-m, 6.1 kgf-m)
Front wheel axle pinch bolt	16 lbf-ft (22 N-m, 2.2 kgf-m)
Front wheel brake caliper mounting bolt	33 lbf-ft (45 N-m, 4.6 kgf-m)