This section tells you how to fine tune your motorcycle for maximum performance.

Off-Road Use only

Initial suspension adjustments should be performed after a minimum of 2 hours of easy break-in time.

Follow the instructions given in the rear suspension sag setting section of *Rear Suspension Adjustments* to determine if your combined rider and sprung machine weight (rider fully dressed for competition and machine coolant, oil and fuel levels ready for competition).

Front Suspension Adjustments	
Front Suspension Air Pressure	.144
Front Suspension Damping	
Rear Suspension Adjustments	
Rear Suspension Spring Pre-Load	
(Off-Road Use Only)	.146
Rear Suspension Damping	.147
Rear Suspension Race Sag	
(Off-Road Use Only)	.148
Suspension Adjustment Guidelines	
(Off-Road Use Only)	.150
Tuning Tips	.153
Spark Plug Reading (Off-Road Use Only)	.153
Chassis Adjustments	.154
Rear End (Off-Road Use Only)	
Fork Height/Angle (Off-Road Use Only)	.154
Wheelbase (Off-Road Use Only)	.154
Tire Selection for Track Conditions	
(Off-Road Use Only)	.155
Personal Fit Adjustments	.156
Control Positioning (Off-Road Use Only)	.156
Handlebar Position (Off-Road Use Only)	.156