

Specifications

■ Main Components

| | | |
|----------------------------|---|-----------------|
| Overall length | 76.0 in (1,930 mm) | |
| Overall width | 29.1 in (740 mm) | |
| Overall height | 43.3 in (1,100 mm) | |
| Wheelbase | 51.8 in (1,315 mm) | |
| Minimum ground clearance | 5.3 in (135 mm) | |
| Caster angle | 27° 00' | |
| Trail | 3.4 in (86 mm) | |
| Curb weight | 50 STATE (meets California) | 293 lb (133 kg) |
| | Canada model | 291 lb (132 kg) |
| Maximum weight capacity *1 | 355 lb (161 kg) | |
| Maximum luggage weight *2 | 29 lb (13 kg) | |
| | Center compartment | 22 lb (10 kg) |
| | Front box | 2.2 lb (1.0 kg) |
| Passenger capacity | Rider and 1 passenger | |
| Minimum turning radius | 6.5 ft (1.98 m) | |
| Displacement | 9.3 cu-in (153 cm ³) | |
| Bore x stroke | 2.28 x 2.28 in (58.0 x 57.9 mm) | |
| Compression ratio | 10.6:1 | |
| Fuel | Unleaded gasoline Recommended fuel octane number: Pump Octane Number (PON) 86 or higher | |

| | |
|-------------------|----------------------------|
| Tank capacity | 2.11 US gal (8.0 L) |
| Battery | GTZ8V |
| | 12 V-7.0 Ah (10 HR) |
| Primary reduction | V-Matic (2.4: 1 ~ 0.80: 1) |
| Final reduction | 10.751 |

*1: Including rider, passenger, all luggage, and accessories.

*2: Includes the weight of the luggage and added accessories.