

■ Service Data

Tire size	Front	3.00-21 51S
	Rear	4.60-18 63S
Tire type		Bias-ply, tube
Recommended Tire	Front	DUNLOP K850 BRIDGESTONE TW-301
	Rear	DUNLOP K850 BRIDGESTONE TW-52
Tire air pressure	Front	22 psi (150 kPa, 1.50 kgf/cm <sup>2</sup> )
	Rear	22 psi (150 kPa, 1.50 kgf/cm <sup>2</sup> )
Minimum tread depth	Front	0.12 in (3.0 mm)
	Rear	0.12 in (3.0 mm)
Spark plug	(standard)	DPR8EA-9 (NGK) X24EPR-U9 (DENSO)
	(cold climate)	DPR7EA-9 (NGK) X22EPR-U9 (DENSO)
	(for extend high speed riding)	DPR9EA-9 (NGK) X27EPR-U9 (DENSO)
	Spark plug gap	0.031 to 0.035 in (0.80 to 0.90 mm)
Idle speed		1,300 ± 100 rpm

Recommended engine oil	API Service Classification SG or higher except oils labeled as energy conserving on the circular API service label, SAE 10W-30, JASO T 903 standard MA, Pro Honda GN4 4-stroke oil (USA & Canada) or Honda 4-stroke oil (Canada only), or an equivalent motorcycle oil	
	After draining	2.0 US qt (1.9 liters)
Engine oil capacity	After draining & engine oil filter change	2.06 US qt (1.95 liters)
	After disassembly	2.4 US qt (2.3 liters)
Recommended brake fluid	Honda DOT 4 Brake Fluid	
Recommended drive chain lubricant	Pro Honda HP Chain Lube	
Drive chain slack	1 3/8 to 1 3/4 in (35 to 45 mm)	
Standard drive chain	RK 520MOZ6 or DID 520V8	
	No. of links	110
Standard sprocket sizes	Engine sprocket	15T
	Rear wheel sprocket	45T