

TOOLS

- NOTES: 1. Equivalent commercially available.
 2. Alternative tool.
 3. Newly designed tool.
 4. Not available in U.S.A

| DESCRIPTION | TOOL NUMBER | REMARKS | REF. SEC. |
|------------------------------------|---------------|--|-----------|
| Fuel pressure gauge | 07406-0040003 | NOTE 2: 07406-0040002 | 5 |
| Oil pressure gauge set | 07506-3000000 | NOTE 1 | 4 |
| Oil pressure gauge attachment | 07510-MJ10100 | NOTE 1 | 4 |
| Clutch center holder | 07724-0050002 | NOTE 1 | 9 |
| Flywheel holder | 07725-0040000 | NOTE 1 | 10 |
| Rotor puller | 07733-0020001 | NOTE 2: 07933-3950000 | 10 |
| Attachment, 32 X 35 mm | 07746-0010100 | | 9, 14 |
| Attachment, 37 X 40 mm | 07746-0010200 | | 9, 14 |
| Attachment, 42 X 47 mm | 07746-0010300 | | 13, 14 |
| Attachment, 52 X 55 mm | 07746-0010400 | | 14 |
| Attachment, 28 X 30 mm | 07746-1870100 | | 14 |
| Attachment, 22 X 24 mm | 07746-0010800 | | 14 |
| Inner driver C | 07746-0030100 | | 11 |
| Attachment, 25 mm I.D. | 07746-0030200 | | 12 |
| Outer driver, 37mm | 07ZMD-MBW0200 | | 14 |
| Pilot, 17 mm | 07746-0040400 | | 9, 14 |
| Pilot, 20 mm | 07746-0040500 | | 13, 14 |
| Pilot, 35 mm | 07746-0040800 | | 9 |
| Pilot, 28 mm | 07746-0041100 | | 14 |
| Bearing remover shaft | 07GGD-0010100 | | 13, 14 |
| Bearing remover head, 20 mm | 07746-0050600 | | 13, 14 |
| Driver | 07749-0010000 | | 9, 13, 14 |
| Valve spring compressor | 07757-0010000 | | 8 |
| Valve seat cutter | | NOTE 1 | 8 |
| Seat cutter, 27.5 mm (45° IN/EX) | 07780-0010200 | | |
| Flat cutter, 27 mm (32° EX) | 07780-0013300 | | |
| Flat cutter, 30 mm (32° IN) | 07780-0012200 | | |
| Interior cutter, 24 mm (60° IN/EX) | 07780-0010600 | | |
| Cutter holder, 4.5 mm | 07781-0010600 | | |
| Snap ring pliers | 07914-SA50001 | | 15 |
| Steering stem socket | 07916-3710101 | NOTE 2: 07916-3710100 | 13 |
| Ball race remover set | 07953-MJ10000 | | 13 |
| - Attachment, 40 mm | 07953-MJ10100 | | |
| - Driver shaft | 07953-MJ10200 | | |
| Ball race remover, 40 x 245L | 07953-4250002 | | |
| Ball race remover, 44.5 mm | 07946-3710500 | | |
| Steering stem driver | 07946-MB00000 | | 13 |
| Fork seal driver weight | 07947-KA50100 | | 13 |
| Fork seal driver attachment | 07946-KA40200 | | 13 |
| Valve spring compressor attachment | 07959-KM30101 | | 8 |
| Oil filter wrench | 07HAA-PJ70100 | | 3 |
| Peak voltage adaptor | 07HGJ-0020100 | NOTE 2 | 5, 17, 19 |
| | | NOTE 3: Peak voltage tester (U.S.A. only) | 8 |
| Tappet hole protector | 07HMG-MR70002 | | |
| Drive chain tool set | 07HMH-MR10103 | NOTE 3: 07HMH-MR1010B or 07HMH-MR1010C (U.S.A. only) | 3 |
| Valve guide driver | 07HMD-ML00101 | | 8 |
| Valve guide reamer, 4.508 mm | 07HMH-ML00101 | | 8 |
| Compression gauge attachment | 07RMJ-MY50100 | NOTE 1 | 8 |
| Inspection adaptor | 07XMZ-MBW0101 | | 20 |
| ECM test harness | 07YMZ-0010100 | Two required | 5 |
| Valve guide driver | 07743-0020000 | | 8 |
| Driver shaft B | 07964-MB00200 | | 12 |
| Christie battery charger | MC1012/2 | U.S.A. only | 17 |