

Specifications

General		Item	Specifications
Dimensions	Overall length	'90-'93:	2,180 mm (85.8 in)
		After '93:	2,125 mm (83.7 in)
	Overall width	'90-'93:	700 mm (27.6 in)
		After '93:	720 mm (28.3 in)
	Overall height		1,185mm (46.7 in)
	Wheelbase		1,470 mm (57.9 in)
	Seat height		800 mm (31.5 in)
	Footpeg height		350 mm (13.8 in)
	Ground clearance		130 mm (5.1 in)
	Dry weight	'90-'93:	216 kg (476 lbs)
		After '93: (49 state type)	211 kg (465 lbs)
		(California type)	212 kg (467 lbs)
		(Canada type)	210 kg (463 lbs)
	Curb weight	'90-'93:	240 kg (529 lbs)
		After '93: (49 state type)	237 kg (523 lbs)
Frame		(California type)	238 kg (525 lbs)
		(Canada type)	236kg (520 lbs)
	Maximum weight capacity	'90-'93:	189 kg (417 lbs)
		After '93:	
		(49 state/California type)	175 kg (386 lbs)
		(Canada type)	179 kg (395 lbs)
	Frame type		Diamond
	Front suspension		Telescopic fork
	Front wheel travel	'90-'93:	140 mm (5.5 in)
		After '93:	130 mm (5.1 in)
	Rear suspension		Swingarm, Pro-link
	Rear wheel travel		130 mm (5.1 in)
	Rear damper		Gas-filled damper
	Front tire size		120/70 VR17-V250, 120/70 ZR17
	Rear tire size		170/60 VR17-V250, 170/60 ZR17
	Tire brand		
	(Bridgestone) FR/RR	'90:	CYROX-19F/CYROX-16F
		After '93:	BT54F RADIAL G/BT54R RADIAL G
	(Dunlop) FR/RR	'91-'93:	K510FC/K510C
		After '93:	D202FN/D202J
	(Michelin) FR/RR	'90:	A59X (COO)/M59X (AOO)
		After '93:	A89X/M89X
	Front brake		Hydraulic disc brake
	Rear brake		Hydraulic disc brake
	Caster angle		26°
	Trail length	'90-'93:	100 mm (3.9 in)
		After '93:	99 mm (3.9 in)
	Fuel tank capacity	'90-'93:	19 lit. (5.0 US gal, 4.2 Imp gal)
		After '93:	21 lit. (5.5 US gal, 4.6 Imp gal)
	Fuel tank reserve capacity		3.5 lit. (0.92 US gal, 0.77 Imp gal)