⚠WARNING

- **Do not service the exhaust system while it is hot.**

NOTE

- If you plan to remove the muffler only, it is not necessary to remove the centerstand, lower fairing and footpeg holder.
- When fitting the muffler, allow a distance of 25–35 mm (1.0–1.4 in) between the muffler and the rear tire as shown.

Requisite Service

- Center stand removal/installation (page 13-16)
- Right footpeg stay removal/installation (page 14-12)
- Lower fairing removal/installation (page 2-7)

	Procedure	Q'ty	Remarks
	Removal Order		Installation is in the reverse order of removal.
	Muffler:		
(1)	Muffler joint bolt/washer	2/2	
(2)	Muffle clamp	2	At installation, align the clamp slits with the chamber tabs.
(3)	Muffler mounting bolt	1	
(4)	Muffler	1	
	Exhaust Pipe/Chamber:		
(5)	Exhaust pipe band bolt	2	Only loosen.
(6)	Front exhaust pipe joint nut	4	NOTE
(7)	Front exhaust pipe	2	• First install all the fasteners loosely. Next, tighten the joint nuts then tighten the band bolts.
(8)	Chamber joint nut	3	
(9)	Chamber	1	
(10)	Rear exhaust pipe joint nut	4	
(11)	Rear exhaust pipe	1	